

442 B



Overfill prevention valve

Gravity or pumped filling
Two stage positive shut-off
Aluminium
Pressure: 4-8 bar
Thread BSP ISO 228-1

CE EN 13616 Ex II 2G

Art.No.	Size	Flow rate
442B-80 AL	3" F	60-1100 l/min

442-1



Overfill prevention valve

Gravity or pumped filling
Two stage positive shut-off
Aluminium
Pressure: 4-8 bar
Thread BSP ISO 228-1

CE EN 13616 Ex II 1 G c II B x

Art.No.	Size	Flow rate
442-80 AL	3" F	60-1100 l/min

440B EN



Overfill prevention valve

Gravity or pumped filling
Two stage positive shut-off
Aluminium
Pressure: 4-8 bar
Thread BSP ISO 228-1

CE EN 13616 Ex II 1 G c II B x

Art.No.	Size	Flow rate
094971	4" F	93-1250 l/min

441



Adapter

Aluminium
Height 100 mm
Thread BSP ISO 228-1

Art.No.	Size
094976	4" M x 3" M

444-1



Adapter

Aluminium
Thread BSP ISO 228-1

Art.No.	Size
094976-1	4" M x 3" F



446

Overfill prevention valve



Gravity or pumped filling
Two stage positive shut-off
Aluminium
Pressure: 4-8 bar
Thread BSP ISO 228-1

Art.No.	Size	Flow rate
446-50 AL	2" M	60-850 l/min
446-80 AL	3" M	60-850 l/min

CE EN 13616 Ex II 2G

442 S

Overfill prevention valve short version



Maximum fuel storage capacity
Gravity or pumped filling
Two stage positive shut-off
Aluminium
Pressure: 4-8 bar
Thread BSP ISO 228-1

Art.No.	Size	Flow rate
442S-80 AL	3" F	60-1000 l/min

CE EN 13616 Ex II 2G

442 OR

Overfill prevention valve horizontal



Maximum fuel storage capacity
Gravity or pumped filling
Two stage positive shut-off
Aluminium
Pressure: 4-8 bar
Thread BSP ISO 228-1

Art.No.	Size	Flow rate
442OR-80 AL	3" F	60-1000 l/min

CE EN 13616 Ex II 2G

445

Overfill prevention valve for diesel



Gravity filling
Aluminium
Thread BSP ISO 228-1
Maximum pressure: 2 bar

Art.No.	Size	Flow rate
094980	2" M	350 l/min

CE Ex II 2G

440 B

Overfill prevention valve



Gravity filling
Aluminium
Maximum pressure: 0,65 bar
Thread BSP ISO 228-1

Art.No.	Size	Flow rate
094975	3" F	800 l/min
094970	4" F	1000 l/min

CE 



Overfill prevention valve 440B with drop tube

Standard length of the tube: 1500 mm

Upper tube available on request

Art.No.	Size
094974	3" F
094969	4" F

CE 

440

Overfill prevention valve



Gravity filling
Aluminium
Maximum pressure: 0,65 bar
Thread BSP ISO 228-1

Art.No.	Size	Flow rate
092410	2" F	550 l/min
092380	3" F	600 l/min
092390	4" F	800 l/min

CE  

444 A

Overfill prevention valve for diesel



Gravity filling
Aluminium
Maximum pressure: 0,7 bar
Thread BSP ISO 228-1

Art.No.	Size	Flow rate
094979	3" F h.72	700 l/min

CE  



1101

Fill cage



Aluminium
Thread BSP ISO 228-1

Art.No.	Size	Height
094982	4" M	136 mm

1102

Drop tube



Aluminium
Thread: Male BSP ISO 228-1 on one side

Art.No.	Size
1102-80-150	3" h 1500 mm
1102-80-200	3" h 2000 mm
1102-100-150	4" h 1500 mm
1102-100-200	4" h 2000 mm

1102 SUP

Riser pipe with collar and rivets



Aluminium
Thread: Male BSP ISO 228-1 on one side

Art.No.	Size
1102-80-50 SUP	3" h 500 mm
1102-80-100 SUP	3" h 1000 mm
1102-80-150 SUP	3" h 1500 mm
1102-80-200 SUP	3" h 2000 mm

103

Drop tube diffuser



Provides a horizontal laminar flow of fuel in the drop tube

Aluminium

Art.No.	Size	Height
103-50	DN50	63,5 mm



102

Drop tube diffuser



Provides a horizontal laminar flow of fuel in the drop tube

Aluminium
Thread BSP ISO 228-1

Art.No.	Size	Height
102-00	3" BSP F	86 mm
102-01	4" BSP F	90 mm

