





## Carrytank CTK 600

Polyethylene tank for fuel transport

NEW



### Description

Carrytank CTK 600 is the new 600-liter polyethylene tank with padlockable lid for transporting diesel fuel or gasoline. The CTK 600, developed in the digital environment, completes the range of the family of type- approved tanks which began with the CARRYTANK 900+100. It is capable of storing and transporting up to 600 liters of diesel fuel or gasoline in complete safety, and complies with the tests required by ADR/IMDG /ADN/RID. It is designed and tested to withstand the pressure created during transport of fuels and to withstand falls at full load even under conditions of extreme temperature. (-20 °C). Gasoline version is also available.

### Main features

It has forklift pockets for lifting from the bottom at full load and 4 certified eyebolts for lifting at full load even from above. It is compatible with the most common filtration systems and comes with aluminum filling plug, safety valve, level gauge, transfer unit, forklift pockets for lifting, handles for lifting when empty, and recesses for securing straps to the support base.

## Outfittings

### DIESEL FUEL OUTFITTINGS

#### Configuration model AC:

- DC fuel transfer pump, mod. DEVIL40 (12 or 24V), flow rate 40 l/min.
- 4 m of hose.
- Automatic nozzle.
- 6 m of battery power cable with bipolar connector for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

#### Configuration model BC:

- AC fuel transfer pump, mod. DEVIL55 (230 V), flow rate 55 l/min.
- 4 m of hose.
- Automatic nozzle.
- 2 m of power cable with Schuko plug for connection to BC supply (Diesel fuel).
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

#### Configuration model ZC:

- DC fuel transfer pump, mod. 12/24V, flow rate 35/70 l/min
- 4 m of hose.
- Automatic nozzle.
- 4 m of battery power cable with bipolar connector for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

#### Configuration model DF:

- DC fuel transfer pump, mod. DPUMP (12 or 24V), flow rate 60 l/min.
- 4 m of hose.
- Automatic nozzle.
- 6 m of battery power cable with bipolar connector for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

### GASOLINE OUTFITTINGS

#### Configuration model EE:

- 12V Pump mod. EX50 12V ATEX Certified, flowrate 45 lit/min.
- 4 mt antistatic hose.
- ATEX automatic nozzle.
- 5 mt electrical cable with bipolar connector.
- 4 mt grounding cable with crocodile clamps.
- Optional: ATEX digital flow meter.
- Optional: water separator filter.

## Accessories



Digital fuel meter, mod. M24, for Diesel Fuel



ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.



Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.



Digital flow meter for gasoline K24 ATEX



Drip Tray

## Technical data

Model	Capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Thickness (mm)	Empty weight (kg)	Weight with pump unit (kg)
CTK600	600	1,290	860	940	11	65	77

## Loading Plan

Model	Container 20'	Container 40'	Container 40' HC	Std truck 2700h mm
CTK600	20	44	44	50

## Product code

CT	X	X	X	X
<b>Model</b> CT = Carrytank	<b>Fuel</b> K = Diesel and gasoline homologated	<b>Volume</b> 600 = 600 l	<b>Pump</b> A = 40 l/min E = Atex 50 l/min B = 55 l/min D = 60 l/min Z = 40 l/min dual voltage 12/24V	<b>Nozzle</b> F = Automatic 80 l/min C = Automatic 60 l/min E = Automatic Atex 60 l/min

Not all combinations are available

## Approval



Transportable materials	Diesel / UNI1202 Gasoline / UNI1203
Classes ADR	3
Packaging group	II - III